

ПРЕДПРИЯТИЕ МАКСАЭРО

- Производство воздуховодов и систем вентиляции
- Клапаны противопожарные
- Клапаны дымоудаления
- Вентиляторы общепром, дымоудаления, крышные

220056, г. Минск, ул. Стариновская, 15

Тел./факс: +375 17 244-67-44, 258-67-51, 347-73-56, 252-54-27

Velcom: +375 29 603-88-99

E-mail: olegaero@yandex.by

www.maxaero.by



Рукавные фильтры Donaldson Dura-Life (олеофобные)



Replacement Elements Media

Dura-Life® Oleo/Hydrophobic	
Appearance	White
Use	Filter bags
Composition	100% polyester
Area weight (DIN 53854)	340 g/m ²
Thickness (DIN 53855)	1.6 mm
Air permeability (DIN 53887) (ASTM D461)	170 l/dm ² min @ 200 Pa 35 cfm/ft ² @ 0.5" wg
Dimensional stability @ 177°C	<3.0%
Surface finish	None
Additional treatments	Heat set Oleo/Hydrophobic oil and water repellent finish
Surface electrical resistance	Not applicable
BIA category	Not applicable
Temperature (dry heat) Continuous Peaks	135°C 150°C
Chemical resistance Hydrolysis Acids Alkalis Oxidising agents Organic solvents	Poor Good Good Very good Very good
Abrasion resistance	Very good
Supports combustion	Yes
Application field	Whenever the dust has an oil or moisture content, the oleo/hydrophobic treatment improves cake release and prevents premature blinding of the media. It is also beneficial when handling moisture sensitive or hygroscopic materials, preventing 'wetting' of the felt and the formation of nodules on the media surface. The treatment is unaffected by temperature and washing.